

Shanghai Liangxin Electrical Co., Ltd. (Nader)

NDQ2A-63 Series Automatic Transfer Switch Product Specification

(IPD-ENG-DEV-T20 A1 2022-09-14)

Prepared by	Cao Xuehu	date	September 14, 2022
Reviewed by	Zhang Huifeng	date	September 14, 2022
Countersigned by	Zhao Zhenxing	date	September 15, 2022
Approved by	Wang Jili	date	September 26, 2022

Revision History					
Version	Revision Reason/Content	Implementation Date	Prepared by	Reviewed by	Approved by
7	Parameter correction	2022-09-14	Cao Xuehu	Zhao Zhenxing	Wang Jili

4. Main Technical Parameters

Electrical characteristics:

- ▲ Rated working voltage U_e : AC 230 V 2P, AC 400 V 3P 4P
- ▲ Rated frequency of controller Hz: 50 Hz
- ▲ Rated current of frame I_{nm} : 63 A
- ▲ ● Rated short-circuit breaking capacity I_{cn} : 6 kA
- ▲ Rated short circuit making capacity I_{cm} : 9.18 kA
- ▲ Contact switching time max (s): ≤ 1.6 S
- ▲ Switching action time max (s): ≤ 3 S

Operating performance:


- ▲ With electricity: 6,000 times
- ▲ Without electricity: 10,000 times

Utilization category: AC-33iB


5. Normal Working Environment

- ▲ Altitude: ≤ 2000 m.
- ▲ Ambient temperature: $-25\text{ }^{\circ}\text{C} + 70\text{ }^{\circ}\text{C}$.
- ▲ Storage temperature: $-55\text{ }^{\circ}\text{C} + 85\text{ }^{\circ}\text{C}$
- ▲ Protection class: IP20.
- ▲ The product can withstand the effects of wet air, salt mist and oil mist.
- ▲ The maximum gradient is 22.5 ° .
- ▲ The product can be disposed in places that are free from explosive media, media corrosive to metal, insulation damaging gas, and conductive dust.
- ▲ The product should be installed free from snow and rain.

6. Tripping Characteristics



Characteristic Curve of Type C Circuit Breaker



Characteristic Curve of Type D Circuit Breaker

7. Product Wiring Diagram




Figure 2 Schematic Diagram of Two-pole Product Wiring




Figure 3 Schematic Diagram of Three-pole Product Wiring




Figure 4 Schematic Diagram of Four-pole Product Wiring

8. Controller function

Function		Standard type	Type B
Sampling	Voltage sampling	3+1	3+3
Protection function	Overvoltage protection	-	√
	Undervoltage protection	-	√
	Open-phase protection	√	√
	Phase angle detection	-	√
Node input/output	Fire signal Input	√	√
	Fire signal feedback	-	√
	Remote control	-	√
	Common closing output	√	√
	Standby closing output	√	√
	Generator starting output	√	√
	Communication port	-	√
Display	Common power supply	√	√

	Standby power supply	√	√
	Common closing	√	√
	Standby closing	√	√
	Automatic	√	√
	Firefighting	√	√
Operation mode Select	Auto switch and auto recover	√	√
	Auto switch and non-auto recover	-	√
Voltage protection Threshold value	Undervoltage value	-	165±5V
	Overpressure value	-	270±5V
Keys	Automatic/manual	√	√

"√" means the function is available; "-" means no such function

9. Wiring terminal diagram

常用合闸指示 (无源节点)		消防控制 无源短接或DC24V		发电机控制 (无源节点)		备用合闸指示 (无源节点)	
1	2	3(-)	4(+)	5	6	7	8
注: 1,2,5,6,7,8 接线端最大电流 0.5A 220VAC							

Fig. 5 (Standard Controller) Secondary Terminal Wiring Diagram

Standard type: 1-2 Common closing indication nodes; 3-4 Fire control nodes (**short circuit or DC 24 V enables fire protection double opening function**)

5-6 Generator control nodes; 7-8 Standby closing indication nodes (passive node)



Fig. 6 (Type B controller) Secondary terminal wiring diagram

Type B: 1-2 Common closing indication nodes; 3-4 Fire control nodes (**short circuit or DC 24 V enables the fire protection double opening function**)

5-6 Generator control nodes; 7-8 Standby closing indication nodes; 9-10 Fire control feedback signal (passive nodes)

11-15 Remote standby closing position operation

12-15 Remote double position operation

13-15 Remote common closing position operation

14-15 Remote enabling (can only be used after short circuit)

16-17 Communication port (See the communication protocol for the use method of 485 communication port (it is bound in additional volume. Dial up our 400 hotline number for request)).

Warning: For manual operation, the controller must be set in the manual state.

8. Outline and Installation Dimensions




Fig. 7 NDQ2A-63 (Standard type)




Fig. 8 NDQ2A-63 (Type B)

Model & specifications	Overall dimensions (mm)			Installation Dimensions (mm)		
	Length	Width	Height	Length	Width	Mounting hole
NDQ2A-63	250	146	128	210	119	φ6

Note: 1. The limit deviation not indicated with the tolerance dimensions is as per GB/T 1804-v.

2. The external and installation dimensions of NDQ2A-63 2P and 3P are the same as 4P.

9. Installation Mode

To be installed horizontally or vertically

10. Packaging and Storage

Packaging quantity: 1 piece/box. The packaged products should be stored in a warehouse with the ambient temperature of -55°C~+85°C and the corresponding relative humidity below 80% without acidic, alkali or other corrosive gas in the surrounding air. Under the conditions above, the storage period shall be no more than 18 months since the manufacturing date.

11. List of Accessories and Installation

SN	Name	Specification	Quantity
1	Hexagon screw	M5×30	4
2.	Plain washer	M5	8
3	Spring washer	M5	8
4	Hexagon nut	M5	4

12. Precautions

- ★ During installation and wiring of the product, strictly distinguish the incoming, outgoing line end and N-pole, and do not share the neutral line.
- ★ It is prohibited to use this product beyond the normal working conditions, such as the continuous water vapor or condensation without corresponding precautions, flammable or corrosive dust without SCPD cooperation or expected short-circuit current beyond the scope, ultra-high or ultra-low voltage, current beyond the rated value and ultra-high attitude.
- ★ For disconnection of the protective apparatus due to the line or load fault, first carry out troubleshooting and then energize the load.
- ★ During the product use, perform regularly (such as operation every three months) general inspection and switch the power supply once manually or automatically to check whether the product is normal.
- ★ This product has been subject to the insulation test before the factory delivery, and wrong dielectric test will damage the control system. Dielectric test is prohibited with ATS.
- ★ In the wiring of main circuit, the screwdriver torque is ≤ 2.5 N, and excessive torque will result in the screw stripping of the wiring frame for the product.